

RDU MULTI-ZONE POWER SUPPLY

SPECIFICATIONS

Dimensions	22"W x 24"H x 4"D
Weight	40 lbs
Operating Ambient Temp.	32 F to 122 F; 0 C to 50 C
Storage Temp.	-4 F to 122 F; -20 C to 50 C
Operating Humidity	10% to 80% RH non-condensing
Storage Humidity	5% to 95% RH non-condensing
Mounting	Wall Mount
Minimum Top/Bottom Clearance	6"
Electrical Input	277 VAC/1.8A, 50-60Hz 120 VAC/4.2A, 50-60Hz 785 W
Max Power Rating	Class 2 Electrical Device
Compliance	UL 2108 UL 924 Drivers in-series or up to 4 zones
Pre-Wired Zones	



OPTIONS + ADD-ON CONTROLS

Embed Controls	Wattstopper LMRC Series
Emergency Controls	Wattstopper ELCU Series



Note: Base model RDU does not include controls. Can be wired up to 4 zones.

RDUXX-C MULTI-ZONE POWER SUPPLY

SPECIFICATIONS

Dimensions	40.25"W x 27.125"H x 4.375"D
Weight	60 lbs
Operating Ambient Temp.	32 F to 122 F; 0 C to 50 C
Storage Temp.	-4 F to 122 F; -20 C to 50 C
Operating Humidity	10% to 80% RH non-condensing
Storage Humidity	5% to 95% RH non-condensing
Mounting	Wall Mount
Minimum Top/Bottom Clearance	6"
Electrical Input	277 VAC/1.8A, 50-60Hz 120 VAC/4.2A, 50-60Hz 1720 W
Max Power Rating	Class 2 Electrical Device
Compliance	UL 2108 UL 924 Drivers in-series or up to 3 zones
Pre-Wired Zones	



- Wattstopper LMRC Series
- Wattstopper ELCU Series

OPTIONS + ADD-ON CONTROLS

Embed Controls	Wattstopper LMRC Series
Emergency Controls	Wattstopper ELCU Series



Note: Base model RDU does not include controls. Can be wired up to 4 zones.

RDUXX MULTI-ZONE POWER SUPPLY

SPECIFICATIONS

Dimensions	28.5"W x 27.125"H x 4.5"D
Weight	60 lbs
Operating Ambient Temp.	32 F to 122 F; 0 C to 50 C
Storage Temp.	-4 F to 122 F; -20 C to 50 C
Operating Humidity	10% to 80% RH non-condensing
Storage Humidity	5% to 95% RH non-condensing
Mounting	Wall Mount
Minimum Top/Bottom Clearance	6"
Electrical Input	277 VAC/1.8A, 50-60Hz 120 VAC/4.2A, 50-60Hz 1720 W
Max Power Rating	Class 2 Electrical Device
Compliance	UL 2108 UL 924 Drivers in-series or up to 4 zones
Pre-Wired Zones	



OPTIONS + ADD-ON CONTROLS

Embed Controls	Wattstopper LMRC Series
Emergency Controls	Wattstopper ELCU Series



Note: Base model RDU does not include controls. Can be wired up to 4 zones.

RDU-C MULTI-ZONE POWER SUPPLY

SPECIFICATIONS

Dimensions	22"W x 24"H x 4"D
Weight	40 lbs
Operating Ambient Temp.	32 F to 122 F; 0 C to 50 C
Storage Temp.	-4 F to 122 F; -20 C to 50 C
Operating Humidity	10% to 80% RH non-condensing
Storage Humidity	5% to 95% RH non-condensing
Mounting	Wall Mount
Minimum Top/Bottom Clearance	6"
Electrical Input	277 VAC/1.8A, 50-60Hz 120 VAC/4.2A, 50-60Hz 785 W
Max Power Rating	Class 2 Electrical Device
Compliance	UL 2108 UL 924 Drivers in-series or up to 4 zones
Pre-Wired Zones	



- Wattstopper LMRC Series
- Wattstopper ELCU Series

OPTIONS + ADD-ON CONTROLS

Embed Controls	Wattstopper LMRC Series
Emergency Controls	Wattstopper ELCU Series



Note: Base model RDU does not include controls. Can be wired up to 4 zones.